



- Standard
 Required fields: ¹
Information required for processing
- Option field

- ORDER
 QUOTE

Invoice address (stamp or fill in legibly) cust. no. _____

Shipping address (if different from invoice address)

Company _____

Street _____

ZIP/Place _____

Company _____

Street _____

ZIP/Place _____


Type of order


- Self-fitting ² (fully complete the section "Information about the wheelchair"!)
 Mounting at the Alber factory ³ 1592525

Delivery Standard

Consignment _____

- e-motion M25** – Drive wheel size 22 " 1592520
 e-motion M25 – Drive wheel size 24 " 1592521
 e-motion M25 – Drive wheel size 26 " 1592522
 without remote control 1592524
- Power stages not switchable
 - Rollback delay cannot be activated

Seat width:
(seat tube measured externally)  _____ cm

Seat height front
(measure to bottom line of seat covering)  _____ cm

Important accessories

- Bracket for mounting to the wheelchair 1467178
 Anti-tippers with jack-up function 1489214 (set of two)

Wheel camber incline (if available)

- 0°
 3°

Wheelchair details

Wheelchair manufacturer (e. g. Meyra) _____

Model (e. g. Eurochair., 1.850) _____

Year of manufacture _____

Version (e. g. Hemi) _____

Drum brakes ⁵ Yes No
↳ Attention: Drum brakes must be removed

- Car restraint system available (please consult with Alber customer service)
 Wheel base extension available

Existing wheel position

- 1 = back
 2 = centre
 3 = front



Notes (mounting, delivery, etc.) _____

E-MOTION®

- Standard **Required fields:** ¹
Information required for processing
- Option field

Tyres

- Schwalbe Right Run (Standard). 1592530
black
- Schwalbe Marathon Plus Evolution 1565894
with SmartGuard puncture protection, black
- Pro Speed puncture-proof solid PU 1" 1592532
black
(+ 300 g per wheel, not available for 22" and 26")
- Puncture-proof with inlay 1 3/8" 1592533
black
(+ 500 g per wheel, not available for 26")

Push rims

- Stainless steel (standard) 1592526
- Coated push rim Tetra 1592527
(not available for 26")
(+250 g per wheel)
- Carbolife CURVE L, 1592528
powder coated, black
(not available for 22")
- Carbolife QUADRO 1592529
Tetra-Gripp coating
(not available for 22" and 26")

Push rim covers (retrofit)

- push rim cover 22" 1592425 (pair)
- push rim cover 24" 1592421 (pair)
- push rim cover 26" 1592426 (pair)

Spoke cover (retrofit)

- Spoke cover 22", Design „Comic“ 1592266 (pair)
- Spoke cover 24", Design „Sphere“ 1592268 (pair)
- Spoke cover 26", Design „Sphere“ 1592269 (pair)
- Spoke cover 24", plain 1592553 (pair)

Accessories

- Ergonomic stub axle 1591500 (pair)
- Transport Axle 1591362
- Conversion of manual wheels to 1565005
1/2" stub axle⁴
- Brake extension kit 1467780 (pair)
- Bracket for ECS remote control 1592743
Easy fitting to the wheelchair

Mounting position bracket for ECS remote control

- Right
- Left (instead of right)



Date _____ / _____ / _____

Signature of ordering party _____

Dated 01.01.2019. All prices before VAT, including packaging ex factory. The general Terms and Conditions of Alber GmbH apply, subject to changes.

- 1) In order to smoothly and quickly process your order we require ALL information in the fields highlighted in blue.
- 2) Installation kits can only be shipped to trained specialist dealers (installation training).
- 3) Please send the wheelchair with a copy of this order as soon as possible and freight paid to Alber.
- 4) If the manual wheels are used in combination with e-fix, they must be equipped mit 1/2" with 1/2" stub axles, without drum brakes and tyres of size 1".
- 5) If present, drum brakes must be dismantled as they are not compatible with e-fix drive wheels. The use of standard lever brakes is required.

ISO 13485
BUREAU VERITAS
Certification

